

# Robust aber kompakt: 3 m Sturzschutz – IP67 – 280 g



- Windows CE® 6.0 R3
- 3 m Sturzschutz und IP67
- 280 g leicht und besonders ergonomisch
- 6,9 cm QVGA-Touchdisplay
- Smart Card Reader / Writer

Spezifikationen			
Modell	DT-X8-10E	DT-X8-20E	
<b>CPU</b>	Marvell® PXA320 624MHz		
<b>Betriebssystem</b>	Microsoft® Windows® Embedded CE 6.0 R3 Englische Version		
<b>Strapazierfähigkeit</b>	<b>Sturzschutz</b>	3.0m	
	<b>Staub/Spritzwasserschutz</b>	IP67 (Kompatibel mit IEC60529 Standard)	
	<b>Betriebs-temperatur</b>	-20°C bis 50°C	
<b>Speicher</b>	<b>RAM</b>	128MB	
	<b>ROM</b>	256MB (Frei für User: Ca. 160MB)	
<b>Display</b>	<b>LCD</b>	Blanview® TFT Farb-LCD mit Touchscreen 5,9 cm (2,7 Inch) QVGA (240x320 Pixel)	
	<b>Anzeige</b>	Anzeige 1: Batteriewechsel-Status Anzeige 2: Kabellose Kommunikation und Scan-Status	
<b>Eingabe</b>	<b>Tastatur</b>	23 Tasten, inkl. num. Tasten, CLR-Taste, Abschlusstaste, Cursor-Taste, Power-Taste, Trigger-Taste Fn key, F1 zu F8 Taste, L/R-Taste	
	<b>Scannertasten</b>	3 (Mitte, Links und rechts)	
	<b>Touchscreen</b>	Ja (Resistiver Typ)	
<b>Scanner</b>	<b>Typ</b>	Laser-Scanner	C-MOS Imager
	<b>Auflösung</b>	0.127mm	1D: 0.15mm, Stacked: 0.169mm, Matrix: 0.25mm
	<b>1D</b>	GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, MSI, Interleaved 2of5 (ITF), Industrial 2 of 5	GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, Code32, Code11, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, MSI, Interleaved 2 of 5 (ITF)
	<b>Stacked</b>	GS1 DataBar Stacked, GS1 DataBar Expanded Stacked	GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Code49, PDF417, Micro PDF, Composite, Codablock F, TLC39
	<b>Matrix</b>		Aztec, DataMatrix, Maxicode, QR Code, microQR
<b>Wireless LAN</b>	<b>Standard</b>	IEEE 802.11b (Maximum: 11Mbps), IEEE 802.11g (Maximum: 54Mbps)	
	<b>Sicherheit</b>	WPA2 / AES	
<b>Interface</b>	<b>Bluetooth®</b>	Bluetooth® Version 2.0+EDR kompatibel	
	<b>Karte</b>	microSD Speicherkarte (SDHC) x 1	
	<b>USB Port</b>	Version 1.1 (Host/Client)	
	<b>Audio</b>	Mikrofon: integriert (monaural), Lautsprecher: integriert (monaural)	
<b>Power</b>	<b>Main Power</b>	Large-capacity lithium-ion battery pack (Operating period: Approx. 20 hours*)	Large-capacity lithium-ion battery pack (Operating period: Approx. 18 hours*)
	<b>Memory Backup</b>	Lithium-Batterie (wiederaufladbar) integriert	
<b>Vibrator</b>	Standard		
<b>Größe (BxHxT)</b>	Ca. 65,7 (57,4*) x 187,0 x 32,4 (35,0*) mm *Griff außen		
<b>Gewicht</b>	282g (Inklusive großem Akku)		



Windows® and Windows® Embedded are registered trademarks of the Microsoft Corporation, USA. The Bluetooth trademark is owned by Bluetooth SIG, USA and licensed to Casio Computer Co. Ltd. Other product- or company names are

either trademarks or registered trademarks of the respective owners. This publication carries product description without obligation and is not to be seen as a firm offer. Specifications and design are subject to change without notice.

